



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : B61K 3/00	A1	(11) International Publication Number: WO 00/61418 (43) International Publication Date: 19 October 2000 (19.10.00)
--	----	---

(21) International Application Number: PCT/US00/09269

(22) International Filing Date: 7 April 2000 (07.04.00)

(30) Priority Data:  
60/128,290 8 April 1999 (08.04.99) US(71) Applicant (for all designated States except US): PORTEC  
RAIL PRODUCTS, INC. [US/US]; P.O. Box 38250, 900  
Freeport Road, Pittsburgh, PA 15238-8250 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): URMSON, W., Thomas,  
Jr. [US/US]; 1375 Pittsburgh Road, Valencia, (PA) 16059  
(US). MOSPAN, John, W. [US/US]; 925 Stevendale Drive,  
Pittsburgh, (PA) 15221 (US). LENCO, Frank, T. [US/US]; 96  
North Bryant Avenue, Pittsburgh, (PA) 15202 (US).(74) Agents: REZNICK, Paul, M. et al.; Webb Ziesenheim Logsdon  
Orkin & Hanson, P.C., 700 Koppers Building, 436 Seventh  
Avenue, Pittsburgh, PA 15219-1818 (US).(81) Designated States: AE, AG, AL, AM, AT, AT (Utility model),  
AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU,  
CZ, CZ (Utility model), DE, DE (Utility model), DK, DK  
(Utility model), DM, DZ, EE, EE (Utility model), ES, FI,  
FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID,  
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT,  
LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL,  
PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL,  
TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW,  
ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ,  
UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD,  
RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI  
patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR,  
NE, SN, TD, TG).

Published

With international search report.

(54) Title: TOP OF RAIL APPLICATOR

(57) Abstract

An applicator (10) for applying a friction modifying material to the top of rails (12). The wayside applicator includes an applicator bar (26) that has a dam for holding friction modifying material.

